

DATA SHEET · LEVEL 2 BUFFERED CLUSTER

LYNX 48 · 12-Port Cluster

48 A · 11.5 kW/port · 50 kWh Na-ion · 100 A service

LYNX48-B50N-12C

Highlights

- ✓ 12 × 11.5 kW = 138 kW total cluster output
- ✓ 50 kWh DRACO Na-ion ESS
- ✓ Premium NEMA 4 outdoor enclosure
- ✓ Most popular L2 cluster configuration
- ✓ Workplace, MDU, fleet-depot ready

Built on the XEYAR shared DC bus

Battery-buffered EV chargers built on the patented XEYAR shared DC-bus architecture. Grid input and battery discharge are simultaneous and additive — letting a 100 A service drive high-power EV charging without a transformer upgrade. eMÖTEN CMS guarantees 50% per active port (NEC 625.42(A)). Ships VPP-ready; revenue activates at XEYAR NEXUS launch (2026).

For full family specifications, see the **LYNX** family spec sheet. Project-specific configuration is confirmed in the engineering quote.

Three durable moats with every MÖTEN charger:

- ✓ Free shipping with every MÖTEN charger — delivered to your jobsite worldwide.
- ✓ eMÖTEN CMS included on all MÖTEN hardware — no monthly subscription.
- ✓ Patented XEYAR shared DC-bus architecture — not available from any other manufacturer.

Certified · Compliant · Worldwide

UL · UL 9540 3rd Ed. · UL 1741 · ETL · cUL · CSA · FCC · ENERGY STAR · OCPP 2.0.1 · ISO 15118 · NEC 625.42(A) · NFPA 855 · IBC/IFC

Quote this configuration: LYNX48-B50N-12C

Request a Quote: evfc.com/contact/?topic=bb-quote · Sales:

evfc.com/contact/?topic=bb-sales

[Request a Quote →](#)